

23%
Solids



PRO SHINE MEGA

Floor Finish



Description:

Advanced polymer formulation allows PRO SHINE MEGA to dry to an extremely high gloss. This technology also enables the dried film to hold its gloss without maintenance longer. For use on vinyl, vinyl asbestos, asphalt tile, rubber, linoleum, tile and other floors.

Directions:

May be applied over other hard, non-wax finishes. But for assured results, the old brand of polish should be removed and the new finish applied to a clean, dry floor.

1. Apply finish in straight, even strokes that will cover fully, but not so liberally as to run into spots.

2. Allow to dry completely. Do not re-work finish while it is drying.

3. When dry, an additional coat, or coats, may be applied if needed. Apply each succeeding coat a little less liberally than the previous one.

FUTURE CARE: Regular dry mopping, damp mopping, and burnishing will extend durability. Worn or dirty areas may be cleaned and spot coated without re-coating the entire floor.

Benefits:

- Harmless to the skin
- Easy to use
- Pleasant fragrance
- Cleans floor but will not dull finish

Specifications:

Appearance.....Milky Liquid
 Odor.....Characteristic
 Specific Gravity1.020 ± 0.005
 Boiling Point.....Near 212°F
 pH8.5 ± 0.5
 Flash PointNone to boiling
 StabilityOne year minimum

Distributed by:



Mayagüez
787-833-8440

Hato Rey
787-767-2562

Product Code:

BS113-01	4 Gal. / Case
----------	---------------

Packaging:

BS113-2.5	2 bags (2.5 gal.) / case
-----------	--------------------------

Used For:

Vinyl Tile

Linomeum Floor

Tile Floor

Marble Floor

